





GASOLINE ENGINE HAMMER DRILL / GT-5000HD

(EDP No.338521)



Main Specifications

Engine	Type	: Two Stroke, Forced, Air Cooled, Single Cylinder	Accessories <ul style="list-style-type: none"> ● Hex Key Wrench <ul style="list-style-type: none"> · 4mm 1pc. · 5mm 1pc. · 6mm 1pc. ● Spark Plug Wrench ● Spanner : 10 - 13mm 1pc. ● Side Handle : 1pc. ● Stopper : 1pc. ● Grease : 1pc. ※Remarks: Hammer Drill Bit is not included.
	Displacement	: 46.5cc, ϕ 43x32mm (Inner bore size x stroke)	
	Fuel Tank Capacity	: 1 liter	
	Fuel Mixture Ratio	: 25:1 (gasoline : 2 cycle oil)	
	Revolution (idling)	: 2700 rpm \pm 250	
	Revolution (loaded)	: 9880 rpm	
	Maximum Output	: 2.3Ps/7500 rpm	
	Maximum Torque	: 0.34kg-m/5500	
Compression Rate	: 7.1:1		
Fuel Consumption Rate	: 380g/Ps.h		
Ignition	Type	: Electronic	Applications <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;">  Drill Bit Hammer Drilling </div> <div style="text-align: center;">  Bull Point Crushing </div> <div style="text-align: center;">  Cold Chisel Edging </div> <div style="text-align: center;">  Cutter Asphalt Cutting </div> <div style="text-align: center;">  Scoop Digging </div> <div style="text-align: center;">  Rammer Tamping </div> </div>
	Spark Plug Type	: NGK BPMR6A	
Carburetor	Type	: Diaphragm	
Capacity	Hammer Drill	: 50mm (2"), Shank: "SDSmax"	
Weight	Without fuel	: 17.90kg (39.5lbs) without drill	

GASOLINE ENGINE IMPACT WRENCH / GT-3500GE

(EDP No.338510)

"The Standard" for world railway maintenance.

Main Specifications

Engine	Type	: Two Stroke, Forced, Air Cooled, Single Cylinder
	Displacement	: 46.5cc, ϕ 43x32mm (Inner bore size x stroke)
	Fuel Tank Capacity	: 1 liter
	Fuel Mixture Ratio	: 25:1 (gasoline:2 cycle oil)
	Revolution (idling)	: 2700 rpm \pm 250
	Revolution (loaded, impact)	: 7120 rpm
Revolution (non loaded, max)	: 9880 rpm	
Ignition	Type	: Electronic
	Spark Plug Type	: NGK BPMR6A
Carburetor	Type	: Diaphragm
Impact	Square Driver Size	: 25.4mm (1")
	Fastening Torque Range	: 1030 N.m (Full Throttle:760 ft.lbf) : 800 N.m (Half Throttle:590 ft.lbf)
	Free Speed	: 1200 rpm
Capacity	Bolt Diameter	: 32mm (1 1/4")
Weight	Without fuel	: 19.50kg (42.99 lbs)

Best seller series, this Portable Impact Wrench offers you the most efficiency of outdoor operations of fastening work in its reliability!



GT - 3500GE

Made In Japan